



# INTERNATIONAL LIFT SYSTEMS, L.L.C.

## Specification Guide - D-H Tension

Casing		Casing I.D. Range (IN.)		Packer O.D. (IN.)	Packer I.D. (IN.)	Thread Connection Box up/Pin down	Part Number
O.D. (IN.)	Weight (LBS./FT.)	Min.	Max.				
2-7/8	6.4-6.5	2.375	2.441	2.250	.75	1.315 EUE	40525
4-1/2	9.5-13.5	3.920	4.090	3.750	1.94	2-3/8 EUE	40545
5	11.5-15	4.408	4.560	4.125	1.94	2-3/8 EUE	40550
5	15.0-20.8	4.156	4.408	4.000	1.94	2-3/8 EUE	40551
5-1/2	13-20	4.778	5.044	4.625	1.94	2-3/8 EUE	40555
5-1/2	13-20	4.778	5.044	4.625	2.44	2-7/8 EUE	40556
5-1/2	20-23	4.670	4.778	4.500	1.94	2-3/8 EUE	40557
5-1/2	20-23	4.670	4.778	4.500	2.44	2-7/8 EUE	40558
6	15-20	5.352	5.524	5.188	2.44	2-7/8 EUE	40560
6-5/8	24-32	5.625	5.921	5.500	2.44	2-7/8 EUE	40565
6-5/8	20-24	5.921	6.049	5.750	2.44	2-7/8 EUE	40568
7	17-29	6.184	6.538	6.00	2.44	2-7/8 EUE	40570
7	17-29	6.184	6.538	6.00	3.00	3-1/2 EUE	40573
7-5/8	20-33.7	6.765	7.125	6.625	2.44	2-7/8 EUE	40575
7-5/8	20-33.7	6.765	7.125	6.625	3.00	3-1/2 EUE	40576
8-5/8	24-40	7.725	8.097	7.500	2.50	2-7/8 EUE	40585
8-5/8	24-40	7.725	8.097	7.500	3.00	3-1/2 EUE	40587
9-5/8	29.3-43.5	8.755	9.063	8.500	2.50	2-7/8 EUE	40595
9-5/8	29.3-43.5	8.755	9.063	8.500	3.00	3-1/2 EUE	40597
10-3/4	40-55.5	9.760	10.050	9.500	3.00	3-1/2 EUE	40510
10-3/4	40-55.5	9.760	10.050	9.500	2.50	2-7/8 EUE	40511
13-3/8	48-72	12.347	12.715	12.000	3.00	3-1/2 EUE	40513

Other sizes and connections available on request